

Product availability : Stock - Normally stocked in distribution facility



Price\* : 347.00 USD



### Main

Device application	Standard mill switch Universal mill switch Heavy duty
Device short name	T
Head type	Rotary head
Series name	Severe duty

### Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
[Uimp] rated impulse withstand voltage	2200 V AC UL 2500 V AC CE 2640 V AC CSA
AWG gauge	AWG 22...AWG 12
Base plate style	Style B
Body material	Cast zinc
Cable entry	NPT conduit entry 0.5 in
Contact code designation	A600 P600
Contact form	Form Z SPDT-DB
Contact status	Closed A for CCW position Open A for CW position Open B for CCW position Closed B for CW position
Contacts material	Silver flashed copper
Contact operation	Snap action
Electrical connection	Screw clamp terminal
Maximum actuation speed	50 ft/min with 45° cam angle, levers only 90 ft/min with 45° cam angle, levers only

Maximum displacement angle	90 °
Positive opening	Without
Repeat accuracy	+/- 0.004 in 0.1 mm
Short circuit protection	20 A Bussmann class CC KTK-R-20 non-time delay
Stage of operation	Contactors closed
Switch actuation	CW and CCW
Tilting angle	45 °
Torque value	8 lbf.in
Tripping angle	0 °
Type of operator	Spring return lever arm to be ordered separately Maintained

## Environment

Ambient air temperature for operation	-10...185 °F
Electrical shock protection class	Class 0
IP degree of protection	IP65 IP66 IP67
NEMA degree of protection	NEMA 1/2/4/12/13
Product certifications	CE CSA UL listed
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn
Standards	UL 508
Vibration resistance	10 gn 10...55 Hz

## Ordering and shipping details

Category	21497 - 9007 FT,T OILTIGHT AND FOUNDRY
Discount Schedule	DS1
GTIN	00785901752110
Nbr. of units in pkg.	1
Package weight(Lbs)	2.5
Returnability	N
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1207 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------