



**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:

**XCMD2110L3**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Terminal Type:  
 Enclosure Rating: NEMA 1/2/4X/6/6P/12/13; IP66/67/68  
 Approvals: UL # E164353 - CSA # 164581 - CE Marked  
 Weight: 0.330 kg (0.730 lb)  
 Conforming to Standards: CENELEC EN 50047  
 RoHS: Yes  
 Operating Temperature Range: -13 to 159 ° F  
 Shock Resistance: 25G  
 Vibration Resistance: 5G  
 Max. Actuation Speed : 0.5 m/s  
 Repeat Accuracy: 0.05 mm on tripping points  
 Operating Torque/Force: 8.5 Inch-Ounces (0.06Nm)

**Specification:**

Description: XCMD Limit Switch Metal end plunger  
 Body Style/Type Description: IEC OsiSense Limit Switches XCMD Miniature Modular 30mm Metal Body  
 Head Type: ZCE10 Metal end plunger  
 Lever Arms:  
 Body with Contact Type: ZCMD21 2-pole N.O./N.C. snap action  
 Conduit Thread: ZCMC21L3 Plug-in base with PVR cable 3 Meter  
 Ampere Rating Continuous: 6A  
 Maximum Voltage Rating: 240VAC/250VDC  
 Actuation: Vertical  
 Actuator Action: Momentary  
 Lever Arm Length:  
 Roller Dimension:  
 Roller Material:  
 Contact Configuration: 1 N.O./1 N.C.  
 Contact Operation: Snap Action  
 Connection Type: PVR Cable  
 Head Material: Zamak  
 Positive Opening: Yes  
 Cable Length: 9.8 ft (3m)