

Rittal – The System.

Faster – better – everywhere.

PK Polycarbonate Housings with knockouts – PK 9508.050

Date : May 25, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



PK Polycarbonate Housings with knockouts – PK 9508.050

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Applications: Ambient temperature range: -35°C...+80°C
The specified temperatures can be limited by the installed equipment

Material: Housing: Fiber-glass reinforced polycarbonate
Cover: Fiberglass-reinforced polycarbonate, all-round foamed PU seal
Cover screws: Polyamide
Insulating bungs: Polythene

Color: RAL 7035

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with cover
Cover screws
Insulating bungs for wall mounting screws

Base material: Polycarbonate

Product features

Dimensions: Height: 94 mm (3.7 ")
Width: 130 mm (5.1 ")
Depth: 57 mm (2.2 ")

Cover: gray

Ambient temperature range:	-35°C...+80°C
Cable entry:	Number x metric diameter: 10 x M16/M20
Packaging unit:	4 pc(s).
Weight/packaging unit:	0.88 kg (1.9 lb.)
EAN:	4028177490192
Customs tariff number:	94037000
ETIM 6.0:	EC000261
ETIM 5.0:	EC000712
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	PK Polycarbonate enclosure, WHD: 130x94x57 mm, fibreglass-reinforced polycarbonate, with knockouts, with grey cover
Approvals	
Approvals:	Bureau Veritas C-UL UL
Declarations:	Declaration of conformity