

B3175 - Ring and Bolt Hanger

Size Range: 1/2" (15mm) to 6" (150mm) pipe

Material: Pre-Galvanized Steel


Function: Designed for suspending light-weight non-insulated pipe. (Use with B3222 eye socket or B3224 hanger adjuster).

Standard Finish: Pre-Galvanized

Order By: Part number and finish.



Bolt and Nut Included



Part No.	Pipe Size in. (mm)	C in. (mm)	Bolt Size	Steel Size in. (mm)	Design Load Lbs. (kN)	Approx. Wt./100 Lbs. (kg)
B3175-1/2	1/2" (15)	1 1/16" (27.0)	1/4"-20	18 Ga. x 7/8" (1.2 x 22.2)	275 (1.22)	7.5 (3.4)
B3175-3/4	3/4" (20)	1 3/16" (30.2)	1/4"-20	18 Ga. x 7/8" (1.2 x 22.2)	275 (1.22)	8.0 (3.6)
B3175-1	1" (25)	1 5/16" (33.3)	1/4"-20	18 Ga. x 7/8" (1.2 x 22.2)	275 (1.22)	9.0 (4.1)
B3175-1 1/4	1 1/4" (32)	1 1/2" (38.1)	1/4"-20	18 Ga. x 7/8" (1.2 x 22.2)	275 (1.22)	10.5 (4.7)
B3175-1 1/2	1 1/2" (40)	1 5/8" (41.3)	1/4"-20	18 Ga. x 7/8" (1.2 x 22.2)	275 (1.22)	11.5 (5.2)
B3175-2	2" (50)	1 13/16" (46.0)	1/4"-20	18 Ga. x 7/8" (1.2 x 22.2)	275 (1.22)	13.0 (5.9)
B3175-2 1/2	2 1/2" (65)	2 5/16" (58.7)	5/16"-18	16 Ga. x 1 1/4" (1.5 x 31.7)	500 (2.22)	30.0 (13.6)
B3175-3	3" (80)	2 5/8" (66.7)	5/16"-18	16 Ga. x 1 1/4" (1.5 x 31.7)	500 (2.22)	35.0 (15.9)
B3175-3 1/2	3 1/2" (90)	2 7/8" (73.0)	5/16"-18	16 Ga. x 1 1/4" (1.5 x 31.7)	500 (2.22)	38.5 (17.4)
B3175-4	4" (100)	3 1/8" (79.4)	5/16"-18	16 Ga. x 1 1/4" (1.5 x 31.7)	500 (2.22)	42.0 (19.0)
B3175-5	5" (125)	3 5/8" (92.1)	5/16"-18	16 Ga. x 1 1/4" (1.5 x 31.7)	500 (2.22)	51.0 (23.1)
B3175-6	6" (150)	4 3/16" (106.4)	5/16"-18	16 Ga. x 1 1/4" (1.5 x 31.7)	500 (2.22)	58.5 (26.5)

B3175CT - Ring and Bolt Hanger, DURA-COPPER™ Coated

Size Range: 1/2" (15mm) to 4" (100mm) pipe

Material: Pre-Galvanized Steel


Function: Designed for suspending copper tubing allowing for vertical adjustment. (Use with B3222 eye socket or B3224 hanger adjuster).

Standard Finish: DURA-COPPER™

Order By: Part number and finish.



Bolt and Nut Included



Part No.	Tubing Size in. (mm)	C in. (mm)	Bolt Size	Steel Size in. (mm)	Design Load Lbs. (kN)	Approx. Wt./100 Lbs. (kg)
B3175CT-1/2	1/2" (15)	1 5/16" (33.3)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	8 (3.6)
B3175CT-3/4	3/4" (20)	1 3/8" (34.9)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	8 (3.6)
B3175CT-1	1" (25)	1 3/16" (30.2)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	8 (3.6)
B3175CT-1 1/4	1 1/4" (32)	1 5/16" (33.3)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	10 (4.5)
B3175CT-1 1/2	1 1/2" (40)	1 1/2" (38.1)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	11 (5.0)
B3175CT-2	2" (50)	1 15/16" (49.2)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	11 (5.0)
B3175CT-2 1/2	2 1/2" (65)	2 3/16" (55.6)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	12 (5.4)
B3175CT-3	3" (80)	2 11/16" (68.3)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	14 (6.3)
B3175CT-3 1/2	3 1/2" (90)	2 15/16" (74.6)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	16 (7.2)
B3175CT-4	4" (100)	3 3/16" (81.0)	1/4"-20 x 1"	1/16" x 7/8" (1.6 x 22.2)	200 (.89)	18 (8.1)

All dimensions in charts and on drawings are in inches. Dimensions shown in parentheses are in millimeters unless otherwise specified.