

Catalog No. 9T58K0055



Description DRY TRANSFORMER

UPC No 783173151136

Products > Transformers > Dry Type, Encapsulated Core & Coil > Machine Tool

Core and coil transformers for machine tool applications are used to provide voltage to control devices in applications where regulation and minimum space are important.

- Fully encapsulated coil is impervious to moisture
- Pressure plate terminals ensure secure connections
- Terminal board is anchored in the epoxy for greater reliability
- Wide variety of fusing options
- Rugged, high-impact plastic terminal board
- Full head #8 brass screws assure quick, easy terminations with maximum connection integrity
- Copper windings
- Flexible design allows input or output voltage to match any application
- CUL, CE, UL approvals
- Available fuse-clips offer simple, low-cost fusing with terminal block models and minimum space are important.

Specifications

Descriptors

Category	Machine Tool
GO Schedule	TQ

Specifications

Phase	1
PriVoltage	240x480
SecVoltage	115
KVA	3.0 KVA
Coil Material	CU
TempRise	115.0 °C
ElecShield	N
SubType	Machine Tool Terminal Blk
Frequency	60 Hz
FrameSize	14475
Net Weight	45
TempClass	180.0 °C
AmbTemp	40.0 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	None
Net Weight	45
Sound	Std

Specifications

GSA Compliance	Yes
----------------	-----

Classifications

UL	Yes
cUL	Yes
CE	No

Dimensions

Width	6.8 in
Depth	8.8 in
Height	5.8 in

Publications

Title	Publication No.	Publication Type
Transformer Outline Drawing	303B947AAP14475	Drawings-Outline and Dimensional
Outline drawing in .pdf format.		
Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.		