

Product availability : Stock - Normally stocked in distribution facility



Price* : 291.00 USD



Main

Device short name	C
Enclosure type	Standard
Head type	Turret head rotary lever type C
Provided equipment	Receptacle
Series name	Heavy duty

Complementary

Line Rated Current	10 A
Body material	Zinc alloy
Contact code designation	Q600 A600
Contact form	Form Z SPDT-DB
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Contacts type and composition	1 NO/1 NC
Maximum displacement angle	90 °
Number of connectors	1 orange 2 red 3 white 4 black 1 ground connection green
Permissible voltage	<= 600 V
Pilot light	Without pilot lamp
Specificity of operator	Standard pre-travel
Switch actuation	CW and CCW
Tilting angle	10 °
Torque value	4 lbf.in
Tripping angle	4 °

Connector type	Mini 5 pins
Type of operator	Spring return lever arm to be ordered separately

Environment

Ambient air temperature for operation	-20...185 °F
Product certifications	CSA CE UL listed

Ordering and shipping details

Category	21499 - 9007 C LIMIT SWITCHES
Discount Schedule	DS1
GTIN	00785901039754
Nbr. of units in pkg.	1
Package weight(Lbs)	1.25
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------