LK4AD10N

TeSys GS - auxiliary contact 100...400A - 1 NO - 1 NC





Main		
Range	TeSys	
Product or component type	Auxiliary contact	
Device application	Connection	
Contacts type and composition	1 NO + 1 NC	

Complementary

Range compatibility	TeSys GS switch
Contact operation	Early-break
[lth] conventional free air thermal current	16 A 104 °F (40 °C)
[le] rated operational current	100 A 200 A 400 A
Mechanical durability	5000000 cycles
Type of operating handle	External frontal External left side External right side

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	l11
GTIN	00785901327417
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	0.39 in (1 cm)	
Package 1 width	0.98 in (2.5 cm)	
Package 1 Length	1.97 in (5 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	

Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months
----------	-----------