



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Transformers](#) > Dry Type, Encapsulated Core & Coil
Transformers,Dry Type, Encapsulated Core & Coil

Product #: 9T58K0050

Short Description: CORE AND COIL SM PWR TRANSFORMERS

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Machine Tool
Phase	1
PriVoltage	240x480
SecVoltage	115
KVA	0.5 KVA
Coil Material	CU
TempRise	80 °C
ElecShield	N
SubType	Machine Tool Terminal Blk
Frequency	60 Hz
UL	Yes
FrameSize	10225
cUL	Yes
CE	No
Width	4.56 in
Depth	5.75 in
Height	3.9 in
TempClass	180 °C
AmbTemp	40 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	None
Sound	Std
GSA Compliance	Yes
GO Schedule	80
List Price	\$79



[View Larger](#)

Publications/Resources

[9T58K0050](#)

Additional Resources for Machine Tool

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)

[Buy Log :8-65](#)

[Control Log : 15-2](#)

Core and coil transformers for machine tool applications are used to provide voltage to control devices in applications where regulation and minimum space are important.

- Fully encapsulated coil is impervious to moisture
- Pressure plate terminals ensure secure connections
- Terminal board is anchored in the epoxy for greater reliability
- Wide variety of fusing options
- Rugged, high-impact plastic terminal board
- Full head #8 brass screws assure quick, easy terminations with maximum connection integrity
- Copper windings
- Flexible design allows input or output voltage to match any application
- CUL, CE, UL approvals
- Available fuse-clips offer simple, low-cost fusing with terminal block models and minimum space are important.