

Product availability : Stock - Normally stocked in distribution facility



Price* : 364.00 USD



Main

Device application	Standard mill switch Universal mill switch Heavy duty
Device short name	T
Head type	Rotary head
Series name	Severe duty

Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
[Uimp] rated impulse withstand voltage	2640 V AC CSA 2200 V AC UL 2500 V AC CE
AWG gauge	AWG 22...AWG 12
Base plate style	Style D
Body material	Cast zinc
Cable entry	NPT conduit entry 0.5 in
Contact code designation	P600 A600
Contact form	Form Z SPDT-DB
Contact status	Open B for CCW position Closed B for CW position Closed A for initial position Open A for CW position Open B for initial position Closed A for CCW position
Contacts material	Silver flashed copper
Contact operation	Snap action
Electrical connection	Screw clamp terminal

Maximum actuation speed	90 ft/min with 45° cam angle, levers only 50 ft/min with 45° cam angle, levers only
Maximum displacement angle	88 °
Positive opening	Without
Repeat accuracy	+/- 0.004 in 0.1 mm
Short circuit protection	20 A Bussmann class CC KTK-R-20 non-time delay
Switch actuation	CW
Tilting angle	14 °
Torque value	12 lbf.in
Tripping angle	12 °
Type of operator	Spring return lever arm to be ordered separately Spring return

Environment

Ambient air temperature for operation	-10...185 °F
Electrical shock protection class	Class 0
IP degree of protection	IP66 IP65 IP67
NEMA degree of protection	NEMA 1/2/4/12/13
Product certifications	UL listed CE CSA
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn
Standards	UL 508
Vibration resistance	10 gn 10...55 Hz

Ordering and shipping details

Category	21497 - 9007 FT,T OILTIGHT AND FOUNDRY
Discount Schedule	DS1
GTIN	00785901752226
Nbr. of units in pkg.	1
Package weight(Lbs)	2.5
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------