

Product data sheet

Characteristics

HOM250PSPD

Surge protection device, Homeline, whole home, 50kA, 120/240 VAC, 1 phase, 3 wire, SPD type 2



Main

Product	Surge protection device
Range	Homeline

Complementary

Surge Current	50 kA
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
Connection	Plug in phase and neutral
MCOV	150 V
Nominal Discharge Current	20 kA
SCCR	22 kA
Height	3.98 in (101 mm)
Width	1.97 in (50 mm)
Depth	2.60 in (66 mm)

Environment

Enclosure Rating	NEMA 2
Enclosure Material	Black Plastic
Standards	UL 1449:ed. 4 CSA C22.2 No 269.1
Ambient Operating	149 °F (65 °C)






Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901520290
Nbr. of units in pkg.	5
Package weight(Lbs)	0.48 lb(US) (0.22 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	3.50 in (8.890 cm)
Package 1 width	5.00 in (12.700 cm)
Package 1 Length	7.50 in (19.050 cm)

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Approximate Dimensions

