



Main

Device short name	MN
Product or component type	Voltage release
Device application	Control
Range compatibility	PowerPact B ComPact NSXm
Voltage release type	Undervoltage release
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC

Complementary

Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Mounting mode	Clip-on
Response time	< 50 ms
Auxiliary connection terminal	Pre-wired 0.00...0.00 in ² (0...0.8 mm ²) AWG 18)stranded copper
Wire stripping length	0.31 in (8 mm)
Cable length	3.28 ft (1 m)

Ordering and shipping details

Category	01136 - PP-B FRAME ACCESSORIES
Discount Schedule	DE2
GTIN	03606485412917
Nbr. of units in pkg.	1
Package weight(Lbs)	0.18 lb(US) (0.08 kg)
Returnability	No
Country of origin	FR

Packing Units

Package 1 Height	1.32 in (3.350 cm)
Package 1 width	2.36 in (6.000 cm)
Package 1 Length	3.23 in (8.200 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	 RECh Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.