

Rittal – The System.

Faster – better – everywhere.

Busbar Supports for stabilizer bar – SV 9676.020

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Busbar Supports for stabilizer bar – SV 9676.020

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Color: RAL 9005

Product features

Suitable for busbar system: Flat-PLS 60

Suitable for busbars: Type: Flat copper busbars

Number of busbars E-Cu per conductor: max.: 4
Note: When using only 1, 2 or 3 bars, the vacant bar slots should be closed using the filler pieces

Cross-section E-Cu busbars: Thickness (max.): 10 mm (0.39 ")
Note on width: At a bar width < 60 mm, the empty gaps in the support should be filled with spacers.

Packaging unit: 1 pc(s).

Weight/packaging unit: 0.7 kg (1.5 lb.)

EAN: 4028177600881

Customs tariff number: 85469010

ETIM 6.0: EC001900

ETIM 5.0:	EC001900
eCl@ss 8.0/8.1:	27400613
eCl@ss 7.0/7.1:	27400613
eCl@ss 6.0/6.1:	27400613
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Busbar support, Flat-PLS 60, for busbar WH: 40-60x10 mm, (stabiliser bar)
Approvals	
Approvals:	ABS DNV-GL
Certificates:	EAC
Declarations:	Declaration of conformity