



Dependable Power for Any Application

hubbell-acmeelectric.com

www.hubbell.com

480Δ - 208Y/120
Snap In Breakers - 480Δ Primary Volts - 208Y/120 Secondary Volts - 3Ø
Panel Tran Zone Power Centers - Three Phase

1087



Catalog #: PTBA3150030LS

PRODUCT FEATURES

Meets or exceeds UL, CSA, NEMA, ANSI, and OSHA standards
Snap-in Breakers
UL Type 3R Enclosure
Shielded for cleaner power
Covered under Acme's 10 year limited warranty

BENEFITS

Fully compliant with NEC 450-3
Designed for indoor and outdoor applications
Electrostatic shield for enhanced protection
Primary and Secondary main circuit breakers provided

UL STANDARD

UL 1062

CSA STANDARD

C22.2 No 47

WARRANTY

Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

kVA:	30.00
Primary Voltage:	480
Secondary Voltage:	208Y/120
Frequency:	60 Hz
ANFC Taps:	-
BNFC Taps:	2
Taps % Steps:	5%
Max Temperature Rise:	115°C
UL Insulation Class:	180°C
Primary Breaker:	ED43B090L (90A)
Secondary Breaker:	Q3100 (100A)

PRODUCT MEASUREMENTS

Height (In./cm):	43.75 (111.1)
Width (In./cm):	33 (83.8)
Depth (In./cm):	13.75 (34.9)

CONFIGURATION

Construction Type:	Encapsulated
Mounting Type:	Wall

PACKAGING

Ship Weight (Lbs/Kg): 680 (308)

COMPLIANCES

UL Standard: UL 1062
UL Listed: File E56936
CSA Standard: C22.2 No 47
CSA Listed: LR7357-39
Warranty: Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf