


**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:

**9016GVG1J11**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Fluid Characteristics: Hydraulic oil, noncorrosive liquids, air, noncorrosive gas  
 Enclosure Rating: NEMA 1  
 Certifications: UL Listed File: E12158 CCN NKPZ - CSA Certified File: LR25490  
 RoHS: No  
 Precision: +/- 1% of the adjustable range over 1,000,000 operations  
 Ambient air temp. for operation: -10 to 185 °F (-23 to 85 °C)  
 Vibration Resistance: 50 g  
 Repeat Accuracy: 0.4% of the adjustable range  
 Operating rate: <math>\leq 120</math> operating cycles per minute  
 Weight: 3.5 lb

**Specification:**

Description: NEMA Square D Vacuum Switches, Power Rated Pressure Switches, 9016GVG  
 Pressure Range: Cut-Out Range 5 - 25 (In. of Hg) / Cut-In Range 0 - 20 Hg (In of Hg)  
 Max. Allowable Pressure: 150 psi  
 Differential Type: Adjustable  
 Output: DPST  
 Electrical Connection: 1/2 - 14 NPT Conduit connection  
 Differential: 5 to 10 in of Mercury  
 Fluid Connection: 1/4in - 18 NPSF Pressure connection  
 Actuator Type: diaphragm  
 Rated Supply voltage: 480VAC  
 Continuous Current Rating: