



Dependable Power for Any Application

hubbell-acmeelectric.com

www.hubbell.com

600Δ - 480Y/277
600Δ Primary Volts - 480Y/277 Secondary Volts - 3Ø
Dry Type Distribution Transformer - Three Phase

1023



Catalog #: T3075K0093BS

PRODUCT FEATURES

- UL listed, CSA certified
- Meet DOE 2016 efficiency requirements
- UL Type 3R with Weather Shield
- Floor Mounted
- Ground Studs for use with non-metallic conduit
- Aluminum Bus termination
- Covered under Acme's 10 year limited warranty

BENEFITS

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

DOE

- Meets or exceed U.S. DOE 10 CFR Part 431

UL STANDARD

- UL 1561

CSA STANDARD

- C22.2 No. 47

WARRANTY

Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

kVA:	75.00
Primary Voltage:	600Δ
Secondary Voltage:	480Y/277
Frequency:	60 Hz
ANFC Taps:	2
BNFC Taps:	4
Taps % Steps:	2.5%
Max Temperature Rise:	150°C
UL Insulation Class:	220°C

PRODUCT MEASUREMENTS

Height (In./cm):	29.41 (74.7)
Width (In./cm):	28.15 (71.5)
Depth (In./cm):	22.37 (56.8)

CONFIGURATION

Construction Type:	Ventilated
Mounting Type:	Floor
Wiring Diagram:	22

PACKAGING

Ship Weight (Lbs/Kg):	600 (272.2)
-----------------------	-------------

COMPLIANCES

DOE:	Meets or exceed U.S. DOE 10 CFR Part 431
UL Standard:	UL 1561
UL Listed:	File E12547
CSA Standard:	C22.2 No. 47
CSA Listed:	LR7357-32
Warranty:	Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf	