



600Δ - 480Y/277
600Δ Primary Volts - 480Y/277 Secondary Volts - 3Ø
Dry Type Distribution Transformer - Three Phase

1149



Catalog #: T2A795171S

PRODUCT FEATURES

UL listed, CSA certified
Fully encapsulated core and coil
Meet CSA C802.2 Efficiency
UL Type 3R epoxy encapsulated
Wall Mounted
Ground Studs for use with non-metallic conduit
Copper lead wire terminations
Covered under Acme's 10 year limited warranty

BENEFITS

Quiet operation with sound levels below NEMA standards
Electrostatic shield for enhanced protection

UL STANDARD

UL 506

CSA STANDARD

C22.2 No. 47

WARRANTY

Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf

GENERAL PRODUCT INFORMATION

KVA:	6.00
Primary Voltage:	600Δ
Secondary Voltage:	480Y/277
Frequency:	60 Hz
ANFC Taps:	-
BNFC Taps:	2
Taps % Steps:	5.0%
Max Temperature Rise:	115°C
UL Insulation Class:	180°C

PRODUCT MEASUREMENTS

Height (In./cm):	11.83 (30.0)
Width (In./cm):	14.17 (36.0)
Depth (In./cm):	8.82 (22.4)

CONFIGURATION

Construction Type:	Encapsulated
Mounting Type:	Wall
Knockouts (In./Cm):	0.75-1.25 (1.9-3.2)

Wiring Diagram: 55

PACKAGING

Ship Weight (Lbs/Kg): 140 (63.5)

COMPLIANCES

UL Standard: UL 506
UL Listed: File E79947
CSA Standard: C22.2 No. 47
CSA Listed: LR7357-32
Warranty: Acme Electric Warranty Card
www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf