

Rittal – The System.

Faster – better – everywhere.

CMC III CAN bus connection cable – DK 7030.090

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CMC III CAN bus connection cable – DK 7030.090

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description:	This cable can be used to connect the PU with the CAN-Bus III sensors, III units and III control units. Also for cabling with one another.
Applications:	For connecting the CAN bus units. Information and power distribution systems of the individual CAN bus units.
Supply includes:	Cable holder

Product features

Dimensions:	Length: 0.5 m (20 ")
Operating temperature:	Operation (environment): +0°C...+55°C
Ambient humidity (non-condensing):	Operation (environment): 5 % - 95 %
Interfaces/connections:	Connector (type): RJ45 Connector (type): RJ45
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.03 kg (0.1 lb.)
EAN:	4028177659414
Customs tariff number:	85444290

ETIM 6.0:	EC000313
ETIM 5.0:	EC002627
eCl@ss 8.0/8.1:	27189253
eCl@ss 7.0/7.1:	27189253
eCl@ss 6.0/6.1:	27189253
eCl@ss 5.1/5.1.4:	27189253
Product description (long):	DK CMC III CAN bus connection cable, L: 0,5 m, type: RJ45