

SKU: AH-1

UPC: 0783669004007



Features & Benefits:

Description: Aluminum Compression Tap, Main Range 1/0-6, Tap Range 1-6, Tin Plated, UL

Specs

Additional Class Attributes

| | |
|-------------------------|-----|
| Barrel Marking | Ink |
| Fixing Type | NA |
| ILSCOs Die Index Number | O |
| Replacement Part(s) | NA |

Dimensions

| | |
|----------------|--------|
| Height (IN) | 0.696 |
| Height BX (IN) | 4.25 |
| Length (IN) | 1.81 |
| Length (mm) | 45.974 |
| Weight (LB) | 0.076 |
| Weight BX (LB) | 2.606 |
| Width (IN) | 1.625 |
| Width BX (IN) | 7.75 |
| Width (mm) | 41.275 |

Material and Finish

| | |
|--------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish | Tin |
| Insulation | NA |
| Material | Aluminum |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 25 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | S-588-1 |
| UPC Code | 78366900400 |

Bolt and Screw Sizes

| | |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

Testing Standards

| | |
|--------------------------|---|
| CSA File Number | NA |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number | 453G |
| UL / CULUS Specification | UL 486A/B Listed |
| UL File Number | E158587 |

Environment and Temperature

| | |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

Color

| | |
|------------|--------|
| Color | Silver |
| Color Code | Green |

Conductor Ranges

| | |
|--|-----------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | 1/0 Str - 6 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | 1 Str - 6 Str |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 1/0 Str - 6 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | 1 Str - 6 Str |
| Conductor Range AL Solid (Primary, run, main, line) | NA |

Voltage

| | |
|---------------------------|-------|
| Voltage Rating | 35 kV |
| Voltage Rating with cover | NA |