



**SKU:** CA5RP

**UPC:** 0783669022100

**Features & Benefits:**

**Description:** Aluminum Box-Type Mechanical Lug, Conductor Range 1/0-14 CU, 1/0-12 AL, 1 Hole, Round Boss, Tin Plated

## Specs

### Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.737
Height BX (IN)	2.25
Height (mm)	18.7198
Length (IN)	0.625
Length (mm)	15.875
Mounting Bolt/Stud Size (mm)	26212.8
Mounting Hole Spacing (mm)	0
Size of Boss (IN)	0.228
Size of Boss (mm)	5.7912
Weight (LB)	0.021
Weight BX (LB)	1.965
Width (IN)	0.564
Width BX (IN)	5
Width (mm)	14.3256

### Additional Class Attributes

Anti-Turn Key	No
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Tap
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1
Style of Boss	Round

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

## Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

## Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10-32
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16
Wire Binding Torque	10 - 14 AWG = 35

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366902210

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

## Environment and Temperature

Temperature Rating	75°C
--------------------	------

## Color

Color	Silver
-------	--------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 12 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 12 Sol
Wire Combinations	NA

## Voltage

Voltage Rating	35 kV
----------------	-------

