



SKU: CLNS-4/0-14

UPC: 0783669639544

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 4/0, 1 Hole, 1/4in Bolt Size, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-54
ILSCOs Die Index Number	I-54
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.5
Barrel Length (mm)	38.1
Dimension G (IN)	0.321
Dimension G (mm)	8.1534
Height (IN)	0.727
Height BX (IN)	2.25
Height (mm)	18.4658
Inside Diameter (IN)	0.546
Inside Diameter (mm)	13.8684
Length (IN)	2.866
Length (mm)	72.7964
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.687
Outside Diameter (mm)	17.4498
Strip Length (mm)	39.6748
Tang Length (IN)	0.875
Tang Length (mm)	22.225
Tang Thickness (IN)	0.141
Tang Thickness (mm)	3.5814
Tang Width (IN)	0.999



Tang Width (mm)	25.3746
Weight (LB)	0.122026271708807
Weight BX (LB)	2.132
Width (IN)	0.999
Width BX (IN)	5
Width (mm)	25.3746

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	4/0 Str - 1 Str
Flex Conductor Range	3/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963954

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------



Color

Color

Silver

Color Code

Purple

Voltage

Voltage Rating

35 kV