

**SKU:** CLWN-700-38-1

**UPC:** 0783669686005

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Lug, Conductor Size 700, 2 Holes, 3/8in Bolt Size, 1in Hole Spacing, Long Barrel, Sight Window, Narrow Tang, Tin Plated, UL, CSA



## Specs

### Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-99
ILSCOs Die Index Number	I-99
Mounting Hole Type	Thru
Narrow Tang	Yes
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

### Dimensions

Barrel Length (IN)	2.687
Barrel Length (mm)	68.2498
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	1.295
Height BX (IN)	2
Height (mm)	32.893
Inside Diameter (IN)	0.991
Inside Diameter (mm)	25.1714
Length (IN)	5.493
Length (mm)	139.5222
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (IN)	1
Mounting Hole Spacing (mm)	25.4
Outside Diameter (IN)	1.25
Outside Diameter (mm)	31.75
Strip Length (mm)	69.8373
Tang Length (IN)	1.937
Tang Length (mm)	49.1998
Tang Thickness (IN)	0.33

Tang Thickness (mm)	8.382
Tang Width (IN)	1.235
Tang Width (mm)	31.369
Weight (LB)	0.714163869720334
Weight BX (LB)	4.487
Width (IN)	1.25
Width BX (IN)	6.184
Width (mm)	31.75

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	700 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	700 kcmil - 350 kcmil
Flex Conductor Range	500 G,H,I, K,M 535.3 DLO

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366968600

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

**Environment and Temperature**

Temperature Rating 90°C

**Color**

Color	Silver
Color Code	Pink

**Voltage**

Voltage Rating 35 kV