




SKU: CRA-4/0-38M

UPC: 0783669098396

Features & Benefits:

Description: Copper Mining Lug, Conductor Size 4/0, 1 Hole, 3/8in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Contains DE-OX®	No
Flared End	No
ILSCOs Die Index Number	I-62
Mounting Hole Type	Thru
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Round
Undrilled	No

Dimensions

Barrel Length (IN)	0.725
Barrel Length (mm)	18.415
Dimension G (IN)	0.605
Dimension G (mm)	15.367
Height (IN)	0.875
Height BX (IN)	2.75
Height (mm)	22.225
Inside Diameter (IN)	0.685
Inside Diameter (mm)	17.399
Length (IN)	2.65
Length (mm)	67.31
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.402
Mounting Hole Diameter (mm)	10.2108
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.815
Outside Diameter (mm)	20.701
Tang Length (IN)	1.23
Tang Length (mm)	31.242
Tang Thickness (IN)	0.13
Tang Thickness (mm)	3.302
Tang Width (IN)	1.2
Tang Width (mm)	30.48
Weight (LB)	0.112
Weight BX (LB)	5.847



Width (IN)	1.2
Width BX (IN)	6
Width (mm)	30.48

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA
Flex Conductor Range	4/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366909839

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	No
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------



Color

Color

Silver

Color Code

Yellow

Voltage

Voltage Rating

35 kV