



**SKU:** CSWS-2-38

**UPC:** 0783669633092

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Lug, Conductor Size 2, 1 Hole, 3/8in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-33
ILSCOs Die Index Number	I-33
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

### Dimensions

Barrel Length (IN)	0.625
Barrel Length (mm)	15.875
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	0.451
Height BX (IN)	2.25
Height (mm)	11.4554
Inside Diameter (IN)	0.312
Inside Diameter (mm)	7.9248
Length (IN)	1.786
Length (mm)	45.3644
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.421
Outside Diameter (mm)	10.6934
Strip Length (mm)	17.4498
Tang Length (IN)	0.875
Tang Length (mm)	22.225
Tang Thickness (IN)	0.109
Tang Thickness (mm)	2.7686

Tang Width (IN)	0.599
Tang Width (mm)	15.2146
Weight (LB)	0.0308647334525826
Weight BX (LB)	1.6875
Width (IN)	0.599
Width BX (IN)	5
Width (mm)	15.2146

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	2 Str - 6 Str
Flex Conductor Range	NA

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963309

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Silver
Color Code	Brown

### Voltage

Voltage Rating	35 kV
----------------	-------