



SKU: CSWS-4-38

UPC: 0783669630411

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 4, 1 Hole, 3/8in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-29
ILSCOs Die Index Number	I-29
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	0.5
Barrel Length (mm)	12.7
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	0.373
Height BX (IN)	2.25
Height (mm)	9.4742
Inside Diameter (IN)	0.25
Inside Diameter (mm)	6.35
Length (IN)	1.609
Length (mm)	40.8686
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.343
Outside Diameter (mm)	8.7122
Strip Length (mm)	14.2748
Tang Length (IN)	0.875
Tang Length (mm)	22.225
Tang Thickness (IN)	0.093
Tang Thickness (mm)	2.3622

Tang Width (IN)	0.592
Tang Width (mm)	15.0368
Weight (LB)	0.0213158948385303
Weight BX (LB)	1.9532
Width (IN)	0.592
Width BX (IN)	5
Width (mm)	15.0368

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	4 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	4 Str - 6 Str
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963041

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature



Temperature Rating

90°C

Color

Color

Silver

Color Code

Gray

Voltage

Voltage Rating

35 kV