



SKU: LO-1000

UPC: 0783669578553

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 1000-500, 1 Port, 1 Hole, 1/2in Bolt Size, Seamless, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	1.565
Height BX (IN)	2.25
Height (mm)	39.751
Length (IN)	3.839
Length (mm)	97.5106
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Spacing (mm)	0
Tang Length (IN)	1.875
Tang Length (mm)	47.625
Weight (LB)	1
Weight BX (LB)	3.9
Width (IN)	2
Width BX (IN)	5
Width (mm)	50.8

Material and Finish

Connector Finish	NA
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Bright Dip
Wire Binding Hardware Material	Brass

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	375

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366957855

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Wire Combinations	NA

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Voltage

Voltage Rating	35 kV
----------------	-------