



**SKU:** NB-350-36-W/R16

**UPC:** 0783669698794

**Features & Benefits:**

**Description:** Aluminum Neutral Bar, Dual Rated, Main Conductor Range 350-6, Tap Range 4-14, 36 Tap Ports, 2 Holes, #10-32 Bolt, Tin Plated, UL, CSA, Includes R-16 Mounting Block

## Specs

### Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Tap
Number of Conductors	5
Number of Mounting Holes	2
Number of Poles	1
Number of Ports Tap	36
Replacement Part(s)	R-16, E-153
Type of Accessory	NBST-2/0

### Dimensions

Dimension G (IN)	0.375
Dimension G (mm)	9.525
Drive Size Main	3/8
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	Slotted
Height (IN)	2.513
Height BX (IN)	3.125
Height (mm)	63.8302
Length (IN)	2.795
Length (mm)	70.993
Mounting Bolt/Stud Size (mm)	26212.8
Mounting Hole Diameter (IN)	0.282
Mounting Hole Diameter (mm)	7.1628
Mounting Hole Spacing (IN)	1.694
Mounting Hole Spacing (mm)	43.0276
Weight (LB)	0.828
Weight BX (LB)	0.9613
Width (IN)	4.73
Width BX (IN)	3.875
Width (mm)	120.142

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum



Wire Binding Hardware Finish  
Wire Binding Hardware Material

Tin  
Aluminum

### Additional Technical Specifications

Conductor Type Solid

### Bolt and Screw Sizes

Mounting Bolt/Stud Size #10-32  
Number of Wire Binding Screws per Port 1  
Wire Binding Screw Size 3/4  
Wire Binding Torque 375

### General

Bag Quantity 1  
Carton Quantity Description STD PACK QTY 1  
Dual Rated Yes  
NEMA Code S-588-3  
UPC Code 78366969879

### Testing Standards

CSA File Number LR-29601  
CSA Standard C22.2 No. 65-03  
Prop65 Compliance WARNING: Cancer and Reproductive Harm - [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)  
ROHS Indicator IND  
UL Control Number NA  
UL / CULUS Specification UL 486A/B Recognized  
UL File Number E6207

### Color

Color Silver

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load) 10 Sol - 14 Sol  
Conductor Range AL Stranded (Primary, run, main, line) 350 kcmil - 6 Str  
Conductor Range AL Stranded (Secondary, tap, load) 4 Str - 14 Str  
Conductor Range CU Solid (Primary, run, main, line) NA  
Conductor Range CU Solid (Secondary, tap, load) 10 Sol - 14 Sol  
Conductor Range CU Stranded (Primary, run, main, line) 350 kcmil - 6 Str  
Conductor Range CU Stranded (Secondary, tap, load) 4 Str - 14 Str  
Conductor Range AL Solid (Primary, run, main, line) NA

### Voltage

Voltage Rating 600 V