



SKU: NB-350-42

UPC: 0783669698855

Features & Benefits:

Description: Aluminum Neutral Bar, Dual Rated, Main Conductor Range 350-6, Tap Range 4-14, 42 Tap Ports, 2 Holes, #10-32 Bolt, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Tap
Number of Conductors	4
Number of Mounting Holes	2
Number of Poles	1
Number of Ports Tap	42
Replacement Part(s)	E-153
Type of Accessory	R-16

Dimensions

Dimension G (IN)	0.234
Dimension G (mm)	5.9436
Drive Size Main	3/8
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	Slotted
Height (IN)	1.513
Height BX (IN)	2.25
Height (mm)	38.4302
Length (IN)	2.531
Length (mm)	64.2874
Mounting Bolt/Stud Size (mm)	26212.8
Mounting Hole Diameter (IN)	0.219
Mounting Hole Diameter (mm)	5.5626
Tang Length (IN)	0.757
Tang Length (mm)	19.2278
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498
Tang Width (IN)	1
Tang Width (mm)	25.4
Weight (LB)	0.512
Weight BX (LB)	1.412
Width (IN)	5.354
Width BX (IN)	5
Width (mm)	135.9916

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10-32
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/4
Wire Binding Torque	375

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366969885

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	4 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	4 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage



Voltage Rating

600 V