



**SKU:** PED4-350SS-DB

**UPC:** 0783669712247

**Features & Benefits:**

**Description:** SafetySub Insulated Multi-Tap Connector, Dual Rated, Direct Burial, Conductor Range 350-12, 4 Ports, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	4
Number of Poles	1
Number of Ports / Wireways	4
Replacement Part(s)	R2314C00A - PLUG FOR ROCKET SEAL, R2315C00A - SCREW PORT PLUG

### Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.459
Height BX (IN)	3.5
Height (mm)	62.4586
Length (IN)	4.424
Length (mm)	112.3696
Weight (LB)	0.813936771820858
Weight BX (LB)	3.7132
Width (IN)	4.68
Width BX (IN)	5.875
Width (mm)	118.872

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation Material	TPE (thermoplastic elastomer)
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/8

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	78366971224

### Testing Standards

ANSI Specification	ANSI C119.1
CSA File Number	LR-29601
CSA Standard	C22.2 No. 198.2
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	88X4
UL / CULUS Specification	UL 486D Listed
UL File Number	E125087

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 12 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 12 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 12 Sol

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Black
-------	-------

### Voltage

Voltage Rating	600 V
----------------	-------