



Fig. 1



Fig. 2

**SKU:** SSKC-6-Z

**UPC:** 0783669857603

**Features & Benefits:**

**Description:** Watertight Underground Splice Kit, Dual Rated, Conductor Size 6, Includes (1) SS-350-Z Cover and (1) ASN-6 Sleeve

## Specs

### Additional Class Attributes

<b>Includes</b>	(1) SS-350-Z, (1) ASN-6
<b>Number of Conductors</b>	2

### Conductor Ranges

<b>Conductor Range AL Solid (Secondary, tap, load)</b>	NA
<b>Conductor Range AL Stranded (Primary, run, main, line)</b>	6 Str
<b>Conductor Range AL Stranded (Secondary, tap, load)</b>	NA
<b>Conductor Range CU Solid (Primary, run, main, line)</b>	NA
<b>Conductor Range CU Solid (Secondary, tap, load)</b>	NA
<b>Conductor Range CU Stranded (Primary, run, main, line)</b>	6 Str
<b>Conductor Range CU Stranded (Secondary, tap, load)</b>	NA
<b>Conductor Range AL Solid (Primary, run, main, line)</b>	NA
<b>Expanded Conductor Range</b>	NA

### Dimensions

<b>Height (IN)</b>	2.2
<b>Height BX (IN)</b>	3.75
<b>Height (mm)</b>	55.88
<b>Length (IN)</b>	14
<b>Length (mm)</b>	355.6
<b>Weight (LB)</b>	0.23798312612136
<b>Weight BX (LB)</b>	1.7092
<b>Width (IN)</b>	4
<b>Width BX (IN)</b>	6.375
<b>Width (mm)</b>	101.6

### Material and Finish

<b>Conductor Material</b>	Aluminum
<b>Insulation Material</b>	EPDM
<b>Material</b>	Aluminum

### Additional Technical Specifications

<b>Conductor Type</b>	Stranded
-----------------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	78366985760

### Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
-------------------	--

### Environment and Temperature

Temperature Rating	90°C
Water tight	Yes

### Color

Color	Silver
-------	--------

### Voltage

Voltage Rating	600 V
----------------	-------