



**SKU:** SX-6

**UPC:** 0783669877205

**Features & Benefits:**

**Description:** Copper Service Entrance Mechanical Lug, Conductor Size 6

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	1

### Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.688
Height BX (IN)	2.25
Height (mm)	17.4752
Length (IN)	0.438
Length (mm)	11.1252
Weight (LB)	0.029
Weight BX (LB)	3.83
Width (IN)	0.338
Width BX (IN)	5
Width (mm)	8.5852

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Bright Dip
Wire Binding Hardware Material	Brass

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
--	---



Wire Binding Screw Size

3/8

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366987720

### Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
RUS Listed	Yes
UL File Number	NA

### Environment and Temperature

Temperature Rating	NA
--------------------	----

### Color

Color	Copper
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

### Voltage

Voltage Rating	35 kV
----------------	-------