




SKU: T3A2-0

UPC: 0783669895902

**Features & Benefits:**

**Description:** Aluminum Mechanical Lug, Conductor Range 1/0-14, 3 Ports, 2 Holes, 3/8in Bolt Size, Tin Plated, UL, CSA



## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | No         |
| Mounting Hole Type         | Thru       |
| Number of Conductors       | 3          |
| Number of Mounting Holes   | 2          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 3          |

### Dimensions

|                              |         |
|------------------------------|---------|
| Dimension G (IN)             | 0.344   |
| Drive Size Main              | NA      |
| Drive Type Main              | Slotted |
| Height (IN)                  | 0.875   |
| Height BX (IN)               | 2.25    |
| Height (mm)                  | 22.225  |
| Length (IN)                  | 2.906   |
| Length (mm)                  | 73.8124 |
| Mounting Bolt/Stud Size (mm) | 965.2   |
| Mounting Hole Diameter (IN)  | 0.437   |
| Mounting Hole Diameter (mm)  | 11.0998 |
| Mounting Hole Spacing (IN)   | 1       |
| Mounting Hole Spacing (mm)   | 25.4    |
| Tang Length (IN)             | 2.156   |
| Tang Length (mm)             | 54.7624 |
| Tang Thickness (IN)          | 0.25    |
| Tang Thickness (mm)          | 6.35    |
| Tang Width (IN)              | 1.938   |
| Tang Width (mm)              | 49.2252 |
| Weight (LB)                  | 0.246   |
| Weight BX (LB)               | 2.3808  |
| Width (IN)                   | 1.938   |
| Width BX (IN)                | 5       |
| Width (mm)                   | 49.2252 |

### Material and Finish

|                    |          |
|--------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish   | Tin      |



|                                |          |
|--------------------------------|----------|
| Insulation                     | NA       |
| Material                       | Aluminum |
| Wire Binding Hardware Finish   | Tin      |
| Wire Binding Hardware Material | Aluminum |

### **Additional Technical Specifications**

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### **Bolt and Screw Sizes**

|                                        |            |
|----------------------------------------|------------|
| Mounting Bolt/Stud Size                | 3/8        |
| Number of Wire Binding Screws per Port | 1          |
| Wire Binding Screw Size                | 7/16       |
| Wire Binding Torque                    | 8 AWG = 40 |

### **General**

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 6 |
| Direct Burial               | No             |
| Dual Rated                  | Yes            |
| NEMA Code                   | S-588-3        |
| UPC Code                    | 78366989590    |

### **Testing Standards**

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator           | IND                                                                                                                 |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### **Environment and Temperature**

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### **Color**

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### **Conductor Ranges**

|                                                        |                  |
|--------------------------------------------------------|------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA               |
| Conductor Range AL Stranded (Primary, run, main, line) | 1/0 Str - 14 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA               |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 14 Sol  |
| Conductor Range CU Solid (Secondary, tap, load)        | NA               |
| Conductor Range CU Stranded (Primary, run, main, line) | 1/0 Str - 14 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA               |
| Conductor Range AL Solid (Primary, run, main, line)    | 10 Sol - 14 Sol  |

Voltage

Voltage Rating

35 kV