




SKU: T4A4-250N

UPC: 0783669912159

Features & Benefits:

Description:Aluminum Mechanical Lug, Conductor Range 250-6, 4 Ports, 4 Holes, 1/2in Bolt Size, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	4
Number of Mounting Holes	4
Number of Poles	1
Number of Ports / Wireways	4

Dimensions

Dimension G (IN)	0.625
Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.187
Height BX (IN)	2.25
Height (mm)	30.1498
Length (IN)	4
Length (mm)	101.6
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.563
Mounting Hole Diameter (mm)	14.3002
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.312
Tang Thickness (mm)	7.9248
Tang Width (IN)	3.687
Tang Width (mm)	93.6498
Weight (LB)	0.625
Weight BX (LB)	1.525
Width (IN)	3.687
Width BX (IN)	5
Width (mm)	93.6498

Material and Finish

Conductor Material	Copper
Connector Finish	Tin



Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/8
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366991215

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating

35 kV