



SKU: XT-6

UPC: 0783669957716

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 6-14, 1 Port, 1 Hole, #10 Bolt Size, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.219
Dimension G (mm)	5.5626
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.682
Height BX (IN)	2.25
Height (mm)	17.3228
Length (IN)	0.975
Length (mm)	24.765
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.203
Tang Length (IN)	0.499
Tang Length (mm)	12.6746
Tang Offset (IN)	0.078
Tang Offset (mm)	1.9812
Tang Thickness (IN)	0.072
Tang Thickness (mm)	1.8288
Tang Width (IN)	0.375
Tang Width (mm)	9.525
Weight (LB)	0.022
Weight BX (LB)	3.11
Width (IN)	0.375
Width BX (IN)	5

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA



Material	Copper
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 18 AWG = 20

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366995771

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str - 18 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA



Voltage

Voltage Rating

35 kV