



B7NFD26A - B7NFD Series - Aluminum Feed-Thru Compact Non-Fused Disconnect Switch Enclosure with ABB Switch - 60A/3P/600VAC/40HP Max

By Killark
Catalog # [B7NFD26A](#)



*Representative Image

B7NFD Series - Aluminum Feed-Thru Compact Non-Fused Disconnect Switch Enclosure with ABB Switch - 60A/3P/600VAC/40HP Max.

Features

- ABB UL508 certified switch supplied for 600VAC, 16, 32, 40, 63 & 80 Amp unit available.
- Enclosures - Copper-free cast aluminum (less than 4/10 of 1% copper content).
- Cover bolts 316 Stainless Steel
- Silicone O-ring gasket.
- Gray powder polyester painted exterior, electrostatically applied.

General

Action	3P
Actuator	Rotary Handle
Catalog Number	B7NFD26A
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Number Of Poles	3
Operating Temperature Celcius Max	40 Degree
Series	B7NFD
UPC	783936009766

Dimensions

Depth	7.8125
Gross Weight with Packaging	24
Height	13.06 in
Weight	23.2 lb
Width	8.125 in

Electrical Ratings

Amperage Rating	60 A
Frequency Rating	60 Hz
Primary Voltage	600 VAC

Conductor Related

Number Of Wires	4
-----------------	---

Certifications And Compliance

CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB+H2, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
Nema Rating	3, 4, 4X, 7(B, C, D), 9(E, F, G)

Product Assets

- [3D Models - B7NFD2 3D Model](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - B7MS, B7MSN, & B7NFD Series CSA Certification](#)
- [Customer Notices - Prop 65 Notice](#)
- [Engineering Drawing - B7NFD2 Engineering Drawing](#)
- [Installation Manuals - B7NFD Series IOM K1327](#)
- [Installation Manuals - B7NFD1-2 IOM K1328](#)
- [Sales Drawings - B7NFD2 Sales Drawing](#)
- [Specifications - B7NFD26A Specification Sheet French](#)
- [Specifications - B7NFD Series Compact Nonfused Disconnect Switches Specification Sheet](#)
- [Specifications - B7NFD26A](#)



A Hubbell brand