

B7NFD2 - B7NFD Series - Aluminum Feed-Thru Compact Non-Fused Disconnect Switch Enclosure - 60/100A

By Killark

Catalog # **B7NFD2**

B7NFD Series - Aluminum Feed-Thru Compact Non-Fused
Disconnect Switch Enclosure - 60/100A.

Application

- The PRISM B7 Series of non-fused disconnect switches are used: in locations made hazardous due to the presence of flammable gasses or vapors or ignitable dusts, fibers, and flyings
- outdoors or indoors in damp, wet, and dirty locations
- in areas where frequent washdowns, heavy rain, or water spray routinely occurs.

General

Catalog Number	B7NFD2
EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Bolted
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Mounting Type	Wall
Number Of Poles	3
Operating Temperature Celcius	40 Degree
Max	
Series	B7NFD
Type	Non-Fused Disconnect
UPC	783936009797

Dimensions

Depth	7.8125
Gross Weight with Packaging	23.2
Height	13.06 in
Weight	23.2 lb
Width	8.125 in

Electrical Ratings



*Representative Image

Frequency Rating

60 Hz

Primary Voltage

600 VAC

Conductor Related

Number Of Wires

4

Certifications And Compliance

CSA File Number

LR11714

Hazardous Rating(s)

- Class I, Divisions 1 & 2, Groups B, C, D
- Class I, Zones 1 & 2, Groups IIB+H2, IIA
- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2, 3, 4, 4X, 7(B, C, D), 9(E, F, G)

Nema Rating

Product Assets

[3D Models - B7NFD2 3D Model](#)

[Catalogs - Killark Catalog](#)

[Certifications - B7MS, B7MSN, & B7NFD Series CSA Certification](#)

[Customer Notices - Prop 65 Notice](#)

[Engineering Drawing - B7NFD2 Engineering Drawing](#)

[Installation Manuals - B7NFD Series IOM K1327](#)

[Installation Manuals - B7NFD1-2 IOM K1328](#)

[Sales Drawings - B7NFD2 Sales Drawing](#)

[Specifications - B7NFD Series Compact Nonfused Disconnect](#)

[Switches Specification Sheet](#)

[Specifications - B7NFD2 Specification Sheet French](#)

[Specifications - B7NFD2 Specification Sheet](#)