



B7NFD63A - B7NFD Series - Aluminum Feed-Thru Compact Non-Fused Disconnect Switch Enclosure with ABB Switch - 63A/3P/600VAC/50HP Max

By Killark
Catalog # [B7NFD63A](#)



*Representative Image

B7NFD Series - Aluminum Feed-Thru Compact Non-Fused Disconnect Switch Enclosure with ABB Switch - 63A/3P/600VAC/50HP Max.

Features

- ABB UL508 certified switch supplied for 600VAC, 16, 32, 40, 63 & 80 Amp unit available.
- Enclosures - Copper-free cast aluminum (less than 4/10 of 1% copper content).
- Cover bolts 316 Stainless Steel
- Silicone O-ring gasket.
- Gray powder polyester painted exterior, electrostatically applied.

General

Action	3P
Actuator	Rotary Handle
Catalog Number	B7NFD63A
EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Bolted
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Mounting Type	
Number Of Poles	3
Operating Temperature Celcius Max	40 Degree
Series	B7NFD
Type	
UPC	783936151663

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	600 VAC

Conductor Related

Number Of Wires	4
-----------------	---

Certifications And Compliance

CSA File Number	LR11714
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups B, C, D Class I, Zones 1 & 2, Groups IIB+H2, IIA Class II, Divisions 1 & 2, Groups E, F, G Class III, Divisions 1 & 2
Nema Rating	3, 4, 4X, 7(B, C, D), 9(E, F, G)

Product Assets

- [3D Models - B7NFD1 3D Model](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - B7MS, B7MSN, & B7NFD Series CSA Certification](#)
- [Customer Notices - Prop 65 Notice](#)
- [Engineering Drawing - B7NFD1 Engineering Drawing](#)
- [Installation Manuals - B7NFD1-2 IOM K1328](#)
- [Installation Manuals - B7NFD Series IOM K1327](#)
- [Sales Drawings - B7NFD1 Sales Drawing](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-B7NFD63A-SPEC-EN | REV 6/2024