



DEDS-30 - DEDS Series, 30 Amp Non-Fused Disconnect Switch

By Killark

Catalog # [DEDS-30](#)

DEDS Series, 30 Amp Non-Fused Disconnect Switch



Features

- Bolted and gasketed cabinet type construction insures the exclusion of conductive or combustible dusts from entering the assembly.
- Enclosure and external handle is copper-free aluminum alloy (less than 4/10 or 1%).
- Cover bolts are stainless steel.
- External handle is vault type with standard provisions for locking in the "OFF" position with up to three padlocks.
- Provisions for locking in "ON" position available as factory modification (Add suffix SU40 to catalog number).
- Eaton (Cutler-Hammer) Type DS Switches.
- Two cast conduit hubs, one top and one bottom.
- Internal disconnect handle mechanism is a sliding plate mounted to the cover.

Specifications

Nema Rating
3R, 4, 9(E, F, G)
UL File Number
E53290
CSA File Number
LR11714
Hazardous Rating(s)

- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2

EU RoHS Indicator
Contact Manufacturer

Conductor

Number Of Poles
3
Number Of Wires
4

Current

Frequency Rating
60 Hz
Primary Voltage
600 VAC/250 VDC

Dimensions

Weight
14.5 lb.
Height
12.125 in
Width
7.375 in
Depth
6.875 in

General

Mounting Type
Wall
UPC
783936116426
Type
Non-Fused Disconnect
Enclosure Type
Bolted
Material
Aluminum, Copper Free (less than 4/10 of 1%)
Series
DEDS Series

Operational

Operating Temperature Celcius Max
40 Degree

Product Assets

[Catalog.\[English\]](#)



A Hubbell brand
© 2026 Hubbell Incorporated. All rights reserved
KILL_CA-DEDS30-SPEC-EN | REV 5/2026