

## DEDS-30

By Killark  
Catalog # **DEDS-30**

DEDS Series, 30 Amp Non-Fused Disconnect Switch.



\*Representative Image

### Features

- Bolted and gasketed cabinet type construction insures the exclusion of conductive or combustible dusts from entering the assembly.
- Enclosure and external handle is copper-free aluminum alloy (less than 4/10 or 1%).
- Cover bolts are stainless steel.
- External handle is vault type with standard provisions for locking in the "OFF" position with up to three padlocks.
- Provisions for locking in "ON" position available as factory modification (Add suffix SU40 to catalog number).
- Eaton (Cutler-Hammer) Type DS Switches.
- Two cast conduit hubs, one top and one bottom.
- Internal disconnect handle mechanism is a sliding plate mounted to the cover.

### General

EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Bolted
Material	Aluminum, Copper Free (less than 4/10 or 1%)
Mounting Type	Wall
Number Of Poles	3
Operating Temperature Celcius Max	40 Degree
Series	DEDS
Type	<ul style="list-style-type: none"><li>Non-Fused Disconnect</li><li>Non-Fused Disconnect</li></ul>
UPC	783936116426

### Dimensions

Depth	6.875
Height	12.125 in
Weight	14.5 lb
Width	7.375 in

### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	600 VAC/250 VDC

### Conductor Related

Number Of Wires	4
-----------------	---

### Certifications and Compliance

CSA File Number	LR11714
Hazardous Rating(s)	<ul style="list-style-type: none"><li>Class II, Divisions 1 &amp; 2, Groups E, F, G</li><li>Class III, Divisions 1 &amp; 2</li></ul>
Nema Rating	3R, 4, 9(E, F, G)
UL File Number	E53290

### Product Assets

[Catalogs - Killark Catalog](#)  
[Certifications - DEDS & XEDS Series UL Certification](#)  
[Customer Notices - Prop 65 Notice](#)



A proud member of the Hubbell Family.