



EKJ-116SS-EX - 1/2" x 16" Flexible Coupling, Stainless Steel, Quad Listed

By Killark
Catalog # [EKJ-116SS-EX](#)

1/2" x 16" Flexible Coupling, Stainless Steel, Quad Listed



Features

- Stainless Steel flexible metal construction
- NPT male fitting (316SS) welded to each end
- Outer Braid (304SS) with inner flex hose of 321SS
- Inner liner of silicone coated fabric
- Certified QUAD listed

Application

For use in hazardous areas where movement or vibration requires a flexible connection or a difficult bend is required in a conduit system.

Specifications

Buy America(n) Qualified	Contact Manufacturer
ATEX File Number	10ATEX11068U
IECEX File Number	10.0057U
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

EU RoHS Indicator

- Class III, Divisions 1 & 2
- Contact Manufacturer

Dimensions

Height	1.34 in
Width	1.34 in
Hub Size	1/2"
Length	20.14 in
Gross Weight with Packaging	2.5
Dimensions	20.14 in x 1.34 in x 1.34 in

General

Color	Silver
UPC	783936073361
Type	Flexible Coupling
Material	Stainless Steel
Finish Type	Natural
Series	EKJ Series

Product Assets

- [Catalog \[English\]](#)
[Installation Manual \[English\]](#)