



ENY-3M - 1" ENY Seal Fitting Iron, Female/Female

By Killark
Catalog # [ENY-3M](#)

1" ENY Seal Fitting Iron, Female/Female

Features

- Minimal turn radius for optimal spacing of both enclosures and conduit
- Large openings for ease of access to conductors for proper dam installation
- Engineered to latest 419 hub specifications for superior continuity and ingress protection
- Integral bushings to protect conductors during installation

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



Dimensions

Hub Size	1"
Length	5 in
Weight	1.93 lb.
Height	0.1 in
Width	10 in
Gross Weight with Packaging	1.93
Dimensions	5 in x 10 in x 0.1 in

General

Color	Gray
Series	ENY Series
UPC	783936111339
Type	Sealing Fitting
Material	Iron
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	5
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)