



ENY-6M - 2" ENY Seal Fitting Iron, Female/Female

By Killark
Catalog # [ENY-6M](#)

2" ENY Seal Fitting Iron, Female/Female

Features

- Minimal turn radius for optimal spacing of both enclosures and conduit
- Large openings for ease of access to conductors for proper dam installation
- Engineered to latest 419 hub specifications for superior continuity and ingress protection
- Integral bushings to protect conductors during installation

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

UL File Number	E10514
CSA File Number	LR11716
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G



EU RoHS Indicator

- Class III, Divisions 1 & 2
Contact Manufacturer

Dimensions

Weight	4.28 lb.
Height	3.5 in
Width	4.125 in
Hub Size	2"
Length	8.75 in
Gross Weight with Packaging	4.28
Dimensions	8.75 in x 4.125 in x 3.5 in

General

Color	Gray
UPC	783936111360
Type	Sealing Fitting
Material	Iron
Finish Type	Powder Epoxy Paint
Series	ENY Series

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)