

ENY-1-T - 1/2" ENY Seal Fitting Aluminum with Nipple Male/Female

By Killark

Catalog # [ENY-1-T](#)

1/2" ENY Seal Fitting Aluminum with Nipple Male/Female



*Representative Image

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

General

Catalog Number	ENY-1-T
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	ENY
Type	Sealing Fitting With Nipple
UPC	783936110509

Dimensions

Gross Weight with Packaging	0.46
Hub Size	1/2"

Certifications And Compliance

CSA File Number	LR11716
Hazardous Rating(s)	<ul style="list-style-type: none">Class I, Divisions 1 & 2, Groups A, B, C, DClass I, Zones 1 & 2, Groups IIC, IIB, IIA

UL File Number

- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2

E10514

Logistics

Carton Quantity 25

Product Assets

[Catalog Page - Fittings: EY Series](#)

[Catalogs - Killark Catalog](#)

[Certifications - ENY Series & Sealing Compound CSA Certificate](#)

[Certifications - EY & EYD Series Sealing Fittings UL Certification](#)

[Certifications - ENY Series Sealing Fittings UL Certifications](#)

[Customer Notices - Prop 65 Notice](#)

[Installation Manuals - Seal Fitting Max Wire Fill IOM K1120](#)

[Installation Manuals - ENY Series IOM K1491](#)

[Literature - ENY Series Expanded Product Offering](#)

[Literature - Hazardous-rated seal-off fittings in expanded trade sizes and with improved design](#)

[Specifications - ENY Spec Sheet](#)

[Specifications - Sealing Materials Specification Sheet](#)

[Specifications - EY-ENY-EYS-EYD Series Sealing Fittings](#)

[Specification Sheet](#)

[Specifications - ENY1T Specification Sheet English](#)

[Specifications - ENY-1-T Specification Sheet French](#)

[Specifications - Sealing Compound & Packing Fiber Specification Sheet](#)