



ENY-5M - 1-1/2" ENY Seal Fitting Iron, Female/Female

By Killark
Catalog # [ENY-5M](#)

1-1/2" ENY Seal Fitting Iron, Female/Female

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

General

Catalog Number	ENY-5M
Color	Gray
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Material	Iron
Series	ENY
Type	Sealing Fitting
UPC	783936111353

Dimensions

Dimensions	7.75 in x 3.5 in x 3.5 in
Gross Weight with Packaging	3.54
Height	3.5 in
Hub Size	1-1/2"
Length	7.75 in
Weight	3.54 lb
Width	3.5 in

Certifications And Compliance

CSA File Number	LR11716
-----------------	---------



*Representative Image

Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
UL File Number	E10514

Product Assets

- [Catalog Page - Fittings: EY Series](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - ENY Series & Sealing Compound CSA Certificate](#)
- [Certifications - EY & EYD Series Sealing Fittings UL Certification](#)
- [Certifications - ENY Series Sealing Fittings UL Certifications](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - Seal Fitting Max Wire Fill IOM K1120](#)
- [Installation Manuals - ENY Series IOM K1491](#)
- [Literature - ENY Series Expanded Product Offering](#)
- [Literature - Hazardous-rated seal-off fittings in expanded trade sizes and with improved design](#)
- [Specifications - ENY Spec Sheet](#)
- [Specifications - ENY5M Specification Sheet English](#)
- [Specifications - Sealing Materials Specification Sheet](#)
- [Specifications - EY-ENY-EYS-EYD Series Sealing Fittings Specification Sheet](#)
- [Specifications - ENY-5M](#)
- [Specifications - Sealing Compound & Packing Fiber Specification Sheet](#)



A Hubbell brand