

EYS-4 - 1 $\frac{1}{4}$ " EYS Seal Fitting Aluminum, Female/Female

By Killark

Catalog # [EYS-4](#)

1 $\frac{1}{4}$ " EYS Seal Fitting Aluminum, Female/Female



*Representative Image

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

General

Catalog Number	EYS-4
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	EYS
Type	Sealing Fitting
UPC	783936110141

Dimensions

Dimensions	10.12 in x 4.68 in x 7.062 in
Gross Weight with Packaging	0.9
Height	7.062 in
Hub Size	1-1/4"
Length	10.12 in
Width	4.68 in

Certifications And Compliance

CSA File Number
Hazardous Rating(s)

LR11716
• Class I, Divisions 1 & 2, Groups C, D
• Class I, Zones 1 & 2, Groups IIB, IIA
• Class II, Divisions 1 & 2, Groups E, F, G
• Class III, Divisions 1 & 2

UL File Number

E10514

Logistics

Carton Quantity 5

Product Assets

- [Catalogs - Killark Catalog](#)
- [Certifications - EYS Series UL Certification](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - KIL_EYS Series Sealing Fittings IOM_K0602](#)
- [Installation Manuals - Seal Fitting Max Wire Fill IOM K1120](#)
- [Specifications - EYS-4 Specification Sheet French](#)
- [Specifications - EYS4 Specification Sheet English](#)
- [Specifications - Sealing Materials Specification Sheet](#)
- [Specifications - EY-ENY-EYS-EYD Series Sealing Fittings Specification Sheet](#)
- [Specifications - Sealing Compound & Packing Fiber Specification Sheet](#)