



FXCS Series Maintained Contact Push/Pull Mushroom Red-Factory Sealed- 1NO/1NC Contact

By Killark
Catalog # [FXCS-OMMR3](#)

FXCS Series - Aluminum Maintained Contact Push/Pull
Mushroom Red-Factory Sealed- 1NO/1NC Contact

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

SEAL-X Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

Specifications

CSA File Number	LR11714, LR11712
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3
UL File Number	E53360, E12379
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Conductor

Number Of Poles	1
-----------------	---



Configuration

Back Box Type	FXB
---------------	-----

Current

Frequency Rating	50/60 Hz
Amperage Rating	10 A

Dimensions

Length	7 in
Weight	3.50 lb.
Height	4.75 in
Width	6 in
Gross Weight with Packaging	3.39
Dimensions	7 in x 6 in x 4.75 in

General

Color	Red
Series	FXCS Series
UPC	783936200255
Type	Aluminum Factory Sealed Cover With Push-Pull Button
Material	Copper-free aluminum

Logistics

Factory Sealed	Factory Sealed
Carton Quantity	1

Operational

Actuator	Single Mushroom Pushbutton
Action	Maintained

Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[French\]](#)