



FXCS Series - Momentary Contact, 2 Mini Push Button- 1 Pilot Light- Red Lens- Cover and Dead-End Box, 1/2" Hub

By Killark
Catalog # [FXCS-1A15](#)

FXCS Momentary Contact, 2 Mini Push Button- 1 Pilot Light- Red Lens- Cover and Dead-End Box, 1/2" Hub

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

SEAL-X Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

Specifications

CSA File Number	LR11714, LR11712
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3
UL File Number	E53360, E12379
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Conductor



Number Of Poles	2
Configuration	
Back Box Type	FXB
Hub Pattern	Dead-End
Current	
Frequency Rating	50/60 Hz
Amperage Rating	10 A
Dimensions	
Hub Size	1/2"
Length	6.63 in
Depth	5.38 in
Height	4.38 in
Width	6 in
Gross Weight with Packaging	4.4
Dimensions	6.63 in x 6 in x 4.38 in
General	
Color	Red-Green P.B. & Red Light
Series	FXCS Series
UPC	783936200774
Type	Factory Sealed
Logistics	
Factory Sealed	Factory Sealed
Operational	
Actuator	Pilot Light & Double Pushbutton
Action	Momentary
Product Assets	
Catalog [English]	
Installation Manual [English]	
Installation Manual [French]	