

FXS Series SPDT (Center Off) Tumbler Switch Cover With Device- Factory Sealed - 20A

By Killark

Catalog # [FXS-5C](#)

FXS Series - Aluminum SPDT (Center Off) Tumbler Switch Cover With Device- Factory Sealed - 20A.



*Representative Image

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splicebox.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

General

Action	SPDT (CNTR OFF)
Actuator	Lever
Ambient Temp. Range	UL: -25 to 40 °C, CSA: -50 to 40 °C, IEC: -20 to 40 °C
Application	
Back Box Type	FXB
Catalog Number	FXS-5C
Color	Gray
	Gris
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	1
Series	FXS
Type	
UPC	783936194844

Dimensions

Depth	3.15
Dimensions	6.63 in x 6 in x 4.38 in
Gross Weight with Packaging	3.2
Height	4.38 in
Length	6.63 in
Width	6 in

Electrical Ratings

Amperage Rating	20 A
Frequency Rating	50/60 Hz

Certifications And Compliance

CSA File Number	LR11712
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups C, D
	Class I, Zones 1 & 2, Groups IIB, IIA
	Class II, Divisions 1 & 2, Groups E, F, G
	Class III, Divisions 1 & 2
Nema Rating	3
UL File Number	E53360, E10501

Logistics

Carton Quantity	5
-----------------	---

Product Assets

Catalogs - Killark Catalog
Certifications - FXS & XS Series UL Certification
Certifications - FXB, FXCS, & FXS Series Control Stations UL Certification
Certifications - FXS, XS, XST Series CSA Certification
Customer Notices - Prop 65 Notice



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-FXS5C-SPEC-EN | REV 6/2024