



FXSX53 - XSD/XSX/FXSD/FXSX Series - FXSX Single Gang Aluminum Manual Motor Starting Switch - 3 Pole 3 Phase - Feed- Thru - Hub Size 3/4 In

By Killark
Catalog # [FXSX53](#)

XSD/XSX/FXSD/FXSX Series - FXSX Single Gang Aluminum
Manual Motor Starting Switch - 3 Pole 3 Phase - Feed-Thru - Hub
Size 3/4 In

Features

- FXSX Series (without overload protection) are ideally suited for across the-line applications where a positive disconnect means is required.
- Factory Sealed so no external seals are required.
- Type 3 (raintight) rated.
- Enclosures are cast copper-free aluminum alloy.
- Operating shaft is stainless steel.
- Multiple gang assemblies available in combination with pilot lights, pushbuttons and switches on request.
- Ground flange joint between bolted cover and box provide required flame path.
- Provisions for padlocking switch in either "ON" or "OFF" position is standard.

Application

Provides manual starting and stopping of small AC or DC motors. Motor running protection when overload heaters are used. FXSX Series (without overload protection) is ideally suited for across-the-line applications where a positive disconnect means is requ

Specifications

CSA File Number	LR11714
Nema Rating	3
UL File Number	E53360 / E12379
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA



- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2

Current

Frequency Rating	60 Hz
Voltage Rating	600 V

Dimensions

Length	8.75 in
Height	6.75 in
Width	5.75 in
Gross Weight with Packaging	4.58
Dimensions	8.75 in x 5.75 in x 6.75 in

General

Product Family	Motor Starters
Series	FXSX Series
UPC	783936198101
Type	Aluminum Manual Motor Starting Switch Without Overload Protection
Material	Aluminum, Copper Free (less than 4/10 of 1%)

Operational

Horsepower - Maximum	5
----------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)