



G Series - Short Single-Turn Potentiometer/Rheostat Operator

By Killark
Catalog # [GO133](#)

G Series - Aluminum Short Single-Turn Potentiometer/Rheostat Operator

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

UL File Number	E150827
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D



EU RoHS Indicator

Dimensions

Height	1.25 in
Width	2.25 in
Length	6.31 in
Gross Weight with Packaging	0.5
Dimensions	6.31 in x 2.25 in x 1.25 in

General

UPC	783936220161
Type	Specialty
Series	GO Series

Operational

Actuator	Potentiometer Operator
Action	Rotary

- Class II, Divisions 1 & 2, Groups E, F, G
 - Class III, Divisions 1 & 2
- Contact Manufacturer