

## **G Series - Short Momentary Contact Double Push Button Operator- Green And Red Buttons With "Start - Stop"/Blank Nameplate - 1NO/1NCcontact Rating**

By Killark

Catalog # [GO22-GR12D](#)



G Series - Aluminum Short Momentary Contact Double Push Button Operator- Green And Red Buttons With "Start - Stop"/Blank Nameplate - 1NO/1NCcontact Rating.

\*Representative Image

### **Features**

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all  $\frac{3}{4}$ "-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

### **General**

Action	Momentary
Actuator	Double Pushbutton
Ambient Temp. Range	UL: -25 to 40 °C, CSA: -50 to 40 °C, IEC: -20 to 40 °C
Application	
Catalog Number	GO22-GR12D
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	2
Series	GO
Type	
UPC	783936222882

### **Dimensions**

Dimensions	6.31 in x 2.25 in x 1.25 in
Gross Weight with Packaging	0.4
Height	1.25 in
Length	6.31 in
Width	2.25 in

### **Electrical Ratings**

Amperage Rating	10 A
Contact Rating	60A INRUSH @ 120 VAC; 30A INRUSH @ 240 VAC; 15A INRUSH @ 480 VAC; 12A INRUSH @ 600 VAC; 0.55A INRUSH @ 125 VDC; 0.275A INRUSH @ 250 VDC; 6A BREAKING @ 120 VAC; 3A BREAKING @ 240 VAC; 1.5A BREAKING @ 480 VAC; 1.2A BREAKING @ 600 VAC; 0.55A BREAKING @ 125 VDC; 0.275A BREAKING @ 250 VDC; 10A CARRYING @ 120 VAC; 10A CARRYING @ 240 VAC; 10A CARRYING @ 480 VAC; 10A CARRYING @ 600 VAC; 2.5A CARRYING @ 125 VDC; 2.5A CARRYING @ 250 VDC.
Frequency Rating	50/60 Hz

### **Certifications And Compliance**

CSA File Number	LR11714
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups C, D
	Class II, Divisions 1 & 2, Groups E, F, G
	Class III, Divisions 1 & 2
UL File Number	E12379

### **Product Assets**

Certifications - GO Series Controls UL Certification
Certifications - GO Series Operators CSA Certificate of Compliance
Customer Notices - Prop 65 Notice



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
KILL\_CA-GO22GR12D-SPEC-EN | REV 6/2024